



12V

33W

SLA

UPS
AGM

12SB25WHR

Rechargeable AGM Sealed Lead Acid Battery

SPECIFICATIONS

Nominal Voltage	12V	
Nominal Power		
10 min rate	33W/cell to 1.60V/cell	
15 min rate	25W/cell to 1.60V/cell	
Nominal Capacity		
20 hour rate	(0.250A to 10.50V)	5Ah
10 hour rate	(0.475A to 10.50V)	4.75Ah
5 hour rate	(0.850A to 10.20V)	4.25Ah
1C	(5A to 9.60V)	3.17Ah
3C	(15A to 9.60V)	2Ah
Weight	Approx. 1.93kg	
Internal Resistance (at 1KHz)	Approx. 19mΩ	
Maximum Discharge Current (5 secs)	75A	

Charge Methods at 25°C

Standby Use

Float Charging Voltage 13.5V to 13.8V
Coefficient -3.0mV/°C/Cell

Maximum Charging Current 1.5A

Operating Temperature Range

Charge -15°C to 40°C
Discharge -15°C to 50°C
Storage -15°C to 40°C

Charge Retention (Shelf Life) at 20°C

1 month 92%
3 months 90%
6 months 80%

Case Material	ABS UL94 HB
Termination	F2 (Faston Tab 250)
Design Life	3-5 years

Classified as a non-spillable battery.
Approved for transportation by:

- Air (IATA/ICAO provision A67)
- Road
- Sea (per IMDG Special Provision 238)



Barcode




9319632520284




DIMENSIONS

mm (inch)




(V)
FOR 12V
BATTERY

Discharge Time VS. Discharge Current (25°C)




CHARACTERISTICS CHARTS


Effect of Temperature on Capacity 25°C (77°F)



Capacity Retention Characteristic



Trickle (or float) Service Life



FEATURES & BENEFITS

- ◆ Industry leading 99.99% pure lead content for superior service life and dependable performance.
- ◆ Specially formulated solder paste to ensure reliable power delivery.
- ◆ Maintenance free technology and non-spillable design.
- ◆ Special grid frame alloy design with outstanding anti-corrosion performance.
- ◆ Higher percentage of tin content compared with the industry standard. Tin extends battery standby life by minimising sulphation (corrosion) especially at higher temperatures.
- ◆ Manufactured by Kung Long Battery (KLB) at facilities in Taiwan and Vietnam. KLB is a leading manufacturer and complies with relevant international quality standards including ISO9001, CE ETL9000, UL1989, OHSAS18001 and ISO17025. KLB supports Green Sustainable supply chain practices.



PERFORMANCE DATA

Discharge Rates in Watts to Various End Voltages at 25°C (77°F)

End Voltage		1.85V	1.80V	1.75V	1.70V	1.67V	1.65V	1.60V
Time								
5	min	37.1	39.8	42.8	45.7	46.8	48	49.3
10	min	26.2	28.3	29.8	31.2	31.5	32.2	33
15	min	22.2	23.7	24.3	24.7	24.8	25	25.1
30	min	12	12.7	13.1	13.3	13.4	13.5	13.6
60	min	5.97	6.45	6.7	6.93	7.05	7.15	7.28
120	min	3.15	3.63	3.85	3.98	4.03	4.1	4.2
180	min	2.43	2.65	2.85	3.03	3.1	3.15	3.25
240	min	1.97	2.18	2.3	2.37	2.4	2.43	2.48
300	min	1.77	1.88	1.98	2.03	2.05	2.07	2.1
600	min	1.02	1.1	1.16	1.19	1.19	1.2	1.22
1200	min	0.532	0.575	0.607	0.618	0.623	0.628	0.637

Discharge Rates in Amperes to Various End Voltages at 25°C (77°F)

End Voltage		1.85V	1.80V	1.75V	1.70V	1.67V	1.65V	1.60V
Time								
5	min	18.7	22.8	25.2	27.1	27.8	28.4	29.3
10	min	13.8	15	15.9	16.7	16.9	17.3	17.8
15	min	10.6	11.3	11.7	12	12.2	12.4	12.6
30	min	5.98	6.31	6.49	6.63	6.68	6.74	6.85
60	min	3.09	3.34	3.48	3.59	3.62	3.67	3.74
120	min	1.72	1.85	1.92	1.98	2.01	2.03	2.06
180	min	1.37	1.46	1.51	1.55	1.57	1.59	1.61
240	min	0.97	1.05	1.09	1.13	1.14	1.16	1.18
300	min	0.863	0.931	0.965	0.986	0.998	1.01	1.03
600	min	0.49	0.532	0.551	0.574	0.577	0.582	0.59
1200	min	0.257	0.291	0.297	0.302	0.304	0.307	0.311

All data on the spec. sheet is an average value:

The tolerance range : $X < 6\text{min}$ (+15%~-15%), $6\text{min} \leq X < 10\text{min}$ (+12%~-12%), $10\text{min} \leq X < 60\text{min}$ (+8%~-8%), $X \geq 60\text{min}$ (+5%~-5%)

Aug2020

Performance may vary depending on application. All specifications are correct at time of creation. All specifications and operation conditions contained in this datasheet are subject to change or improvement without prior notice to the user. This data is for evaluation purposes only. No guarantee is intended or implied by this data. For clarification and updated information, please contact us.